



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 12

FP ABC Texturizing Dry Shampoo

SDS No. : 617630
V001.0

Revision: 26.10.2018
printing date: 08.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FP ABC Texturizing Dry Shampoo

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Dry Shampoo

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Düsseldorf Germany

Henkelstr. 67

40191 Düsseldorf

Phone: +49 211-797-0

E-mail address of person responsible for Safety Data Sheet:

Henkel Cosmetics, e-mail : Rolf.Bayersdoerfer@Henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

Further information is available at Poison Control Centers.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP):

Flammable aerosols Category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

2.2. Label elements (CLP)

Hazard pictogram:



Signal word:

Danger

Hazard statement:

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statement: Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Precautionary statement: Storage

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

SECTION 3: Composition/information on ingredients

3.1. Substances

3.2. Mixtures

Hazardous substances according to CLP (EC) No 1272/2008:

Hazardous substances CAS-No.	EINECS	REACH-Reg No.	Content	Classification
Butane, n- (< 0.1 % butadiene) 106-97-8	203-448-7	01-2119474691-32	>= 70- < 90 %	H220 Flammable gases 1 Gases under pressure
Propane 74-98-6	200-827-9	01-2119486944-21	>= 10- < 20 %	H220 Flammable gases 1 Gases under pressure
Ethanol denatured 64-17-5	200-578-6	01-2119457610-43	>= 3- < 10 %	H225 Flammable liquids 2 H319 Serious eye irritation 2
Isobutane 75-28-5	200-857-2	01-2119485395-27	>= 1- < 10 %	H220 Flammable gases 1 Gases under pressure
Pentane 109-66-0	203-692-4	01-2119459286-30	>= 1- < 2,5 %	H225 Flammable liquids 2 H304 Aspiration hazard 1 H336 Specific target organ toxicity - single exposure 3 H411 Chronic hazards to the aquatic environment 2

For full text of the H - Phrases indicated by codes only see Section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Remove casualty immediately from danger zone. Take off immediately all contaminated clothing.

Inhalation:

Move to fresh air.

Skin contact:

Rinse with water. Take off all clothing contaminated by the product.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse the mouth. Drink 1-2 glasses of water.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:
None known

5.2. Special hazards arising from the substance or mixture
The release of following substances is possible in case of fire:

carbon oxides.
nitrogen oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus.
Wear protective equipment.

Additional information:

Dispose of combustion residues and contaminated fire-fighting water in accordance with statutory regulations.
Collect contaminated fire fighting water separately. It must not enter drains.
In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Take great care to avoid inhalation of the aerosol.

6.2. Environmental precautions

Do not allow to enter drainage system, surface or ground water of not diluted product.
Do not dispose of in wastepaper bin or trash-can.

6.3. Methods and material for containment and cleaning up

Dilute small quantities with large amount of water and rinse.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling advice:
No particular measures required.

Fire and explosion protection information:
Take measures to prevent the build-up of electrostatic charges.
Do not spray onto flame or red-hot objects.
Keep away from sources of ignition - no smoking.

Hygiene measures:
Do not eat, drink or smoke while working.
Immediately remove soiled or soaked clothing.
Wash hands before work breaks and after finishing work.
Keep away from food, beverages and animal feed.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container protected against moisture.
For aerosols: protect from direct sunshine and temperatures above 50°C.
Store far from foodstuffs.

7.3. Specific end use(s)

Dry Shampoo

SECTION 8: Exposure controls/personal protection

Only relevant for professional/industrial use

8.1. Control parameters

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Remarks
Butane 106-97-8	1.000	2.400	Exposure limit(s):	4	TRGS 900
Butane 106-97-8			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Propane 74-98-6	1.000	1.800	Exposure limit(s):	4	TRGS 900
Propane 74-98-6			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethanol 64-17-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethanol 64-17-5	200	380	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Isobutane 75-28-5	1.000	2.400	Exposure limit(s):	4	TRGS 900
Isobutane 75-28-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
PENTANE 109-66-0	1.000	3.000	Time Weighted Average (TWA):	Indicative	ECTLV
Pentane 109-66-0	1.000	3.000	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Pentane 109-66-0			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

8.2. Exposure controls

Engineering controls:

Ensure good ventilation/suction at the workplace.

Respiratory protection:

When processing in open systems with aerosol formation wear suitable respiratory protection to avoid inhalation of aerosol particles.

Hand protection:

Not needed.

Eye protection:

No special measures required if used properly.

Skin protection:

Not needed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The following data apply to the whole mixture:

Appearance	aerosol fine white
Odor	amber, floral, vanilla, woody
pH	Not applicable
Initial boiling point	Not applicable
Flash point	Not applicable
Decomposition temperature	Not applicable
Vapour pressure	Not applicable
Density	Not applicable
Bulk density	Not applicable
Viscosity	Not applicable
Viscosity (kinematic)	Not applicable
Explosive properties	Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Miscible
Solidification temperature	Not applicable
Melting point	Not applicable
Flammability	Not applicable
Auto-ignition temperature	Not applicable
Explosive limits	Not applicable
Partition coefficient: n-octanol/water	Not applicable
Evaporation rate	Not applicable
Vapor density	Not applicable
Oxidising properties	Not applicable
Container pressure (20 °C (68 °F))	3,4 - 3,8 bar
Container pressure (50 °C (122 °F))	6,8 - 7,8 bar

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

None known.

10.3. Possibility of hazardous reactions

See section reactivity

None known.

10.4. Conditions to avoid

Keep away from sources of ignition and naked flames.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

General toxicological information:

The present product is a chemical preparation within the meaning of the chemicals act. The following evaluation has been made on the basis of the toxicological data and content by weight of the individual ingredients.

No information exists about acute toxic, irritative or otherwise harmful effects caused by the product.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethanol denatured 64-17-5	LD50	10.470 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethanol denatured 64-17-5	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	274200 ppm	gas	4 h	rat	not specified
Propane 74-98-6	LC50	> 800000 ppm	gas	15 min	rat	not specified
Ethanol denatured 64-17-5	LC50	124,7 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Isobutane 75-28-5	LC50	260200 ppm	gas	4 h	mouse	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Pentane 109-66-0	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethanol denatured 64-17-5	Category II		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

No data available.

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane 74-98-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propane 74-98-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isobutane 75-28-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobutane 75-28-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l			rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8		inhalation: gas	28 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6		inhalation: gas	28 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Isobutane 75-28-5		inhalation: gas	28 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

The ecological evaluation of the product is based on data from the raw material and/or comparable substances.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	27,98 mg/l	96 h		not specified
Ethanol denatured 64-17-5	LC50	> 12.000 - 16.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Pentane 109-66-0	LC 50	> 0,1 mg/l		Trout family (Salmonidae)	

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	14,22 mg/l	48 h		not specified
Ethanol denatured 64-17-5	EC50	> 100 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Pentane 109-66-0	EC50	9,74 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	7,71 mg/l	96 h		not specified
Ethanol denatured 64-17-5	EC50	> 100 mg/l	24 h	Chlorella pyrenoidosa	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobutane 75-28-5	EC50	7,71 mg/l	96 h		not specified

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol denatured 64-17-5	IC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Ethanol denatured 64-17-5	readily biodegradable	aerobic	> 70 %	5 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Pentane 109-66-0	readily biodegradable	aerobic	87 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Isobutane 75-28-5	2,88	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Pentane 109-66-0	3,45	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Butane, n- (< 0.1 % butadiene) 106-97-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propane 74-98-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethanol denatured 64-17-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isobutane 75-28-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Consider national regulations.

SECTION 14: Transport information**14.1. UN number**

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

14.4. Packing group

ADR
RID
ADN
IMDG
IATA

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

National regulations/information (Germany):

WGK:	1, slightly water-endangering product. (German VwVwS of May 17, 1999) Classification in conformity with the calculation method
Storage class according to TRGS 510:	2B

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is not related to the use of the product, it is based on our current level of knowledge.